

ESD Rubber Tile over Raised Access Floors Maintenance

Flexco ESD Rubber Tile is a low maintenance product that does not require waxes or finishes. The application of a wax or finish will diminish the Dissipative properties of the flooring.

1. Initial Maintenance

- Allow 72 hours after installation for proper curing of the adhesives and/or heat welds
- Remove any coverings used to for floor protection after installation prior to cleaning
- Sweep, dust mop and/or vacuum floor to remove any dirt or particulates accumulated on the floor
- Clean the floor with a high quality Neutral pH cleaner such as Spartan Clean by Peroxy, Spartan Green Solutions All Purpose Cleaner, Spartan Damp Mop or equivalent
- Prepare cleaner according to directions on bottle for a medium duty cleaning
- Using a damp mop, lightly scrub the area to remove any soiling or other contamination
- Burnish using a 180 - 360 RPM with a 3M 4100 White Super Polish Pad while dry to create a shine
- If greater shine is desired, burnish using a 1500 RPM Burnishing Machine* with a 3M Eraser 3600 Burnishing Pad

2. Daily Maintenance

- Sweep, dust mop and/or vacuum floor to remove any dirt or particulates accumulated on the floor
- Remove any spills or other large deposits of dirt and / or debris
- Spot clean any stains by mopping Neutral pH cleaner mixed for general cleaning

3. Regular Maintenance

Keep in mind, if the appearance of the flooring becomes unacceptable; this procedure may require completion more frequently to provide acceptable appearances.

- Sweep, dust mop and/or vacuum floor to remove any dirt or particulates accumulated on the floor
- Clean the floor with a high quality Neutral pH cleaner such as Spartan Clean by Peroxy, Spartan Green Solutions All Purpose Cleaner, Spartan Damp Mop or equivalent
- Prepare cleaner according to directions on bottle for a general duty cleaning
- Using a damp mop, lightly scrub the area to remove any soiling or other contamination
- Burnish using a 180 - 360 RPM with a 3M 4100 White Super Polish Pad while dry to create a shine
- If greater shine is desired, burnish using a 1500 RPM Burnishing Machine* with a 3M Eraser 3600 Burnishing Pad

The use of a highly alkaline, highly acidic or solvent-base cleaners or products will remove color from the flooring or degrade the flooring prematurely. **DO NOT** use sweeping or cleaning agents containing oil or solvents. **DO NOT** allow the solution to work its way beneath the flooring which could result in an adhesive failure. **Caution:** When wet, flooring will become slippery; therefore, use the appropriate warning signs on the floor to eliminate foot or other traffic.

4. Floor Protection Devices

- When moving in appliances or heavy furniture, it is always wise to protect the floor from scuffing and tears by using something to protect the floor
- Use floor protectors under furniture or fixtures to reduce indentation; as a rule of thumb, the heavier the item the wider the floor protection device needed
- Place walk-off mats at outside entrances manufactured with non-staining backs to prevent discoloration

COMPANY INFORMATION

Flexco Corporation
1401 East 6th Street
Tusculumbia, AL, USA 35674
Phone: (800) 633-3151
Fax: (800) 346-9075
Email: info@flexcofloors.com, technical@flexcofloors.com
Internet: www.flexcofloors.com

