

FlexTuft Recycled Rubber Tile Maintenance

Approved Cleaners

Spartan Chemicals Green Solutions All Purpose Cleaner, Spartan Chemicals Clean by Peroxy, Johnson Stride, Taski Profi and/or a Mild Soap & Water Solution for Shampooing

FlexTuft Recycled Rubber Tile is a low maintenance product that does not require waxes or finishes. Lack of regular or routine maintenance will diminish the look and appearance of the flooring.

Initial Maintenance

- Allow 72 hours after installation for proper curing of the adhesives
- Remove any coverings used to for floor protection after installation prior to cleaning
- Sweep and/or vacuum floor with a high CFM vacuum to remove any dirt or particulates accumulated on the floor
- Spot clean and/or shampoo to remove any stains

Daily Maintenance

- Sweep and/or vacuum floor with a high CFM vacuum to remove any dirt or particulates accumulated on the floor
- Spot clean and/or shampoo to remove any stains

Weekly Maintenance

Keep in mind, if the appearance of the flooring becomes unacceptable; this procedure may require completion more frequently to provide acceptable appearances.

- Sweep and/or vacuum floor with a high CFM vacuum to remove any dirt or particulates accumulated on the floor
- Spot clean and/or shampoo to remove any stains
- Use an extractor when necessary to remove any dirt or particulates accumulated on the floor or between strips
- Exterior applications can be hosed and left to dry, if pressure washer is used be careful not to loosen the bond with the adhesive

The use of a highly alkaline, highly acidic or solvent-base cleaners or products will remove color from the flooring or degrade the flooring prematurely. DO NOT use sweeping or cleaning agents containing oil or solvents. DO NOT allow the solution to work its way beneath the flooring which could result in an adhesive failure. Caution: When wet, flooring will become slippery; therefore, use the appropriate warning signs on the floor to eliminate foot or other traffic.

Floor Finishes

There are no known finishes that can be applied to this product. We do not recommend the application of dyes to attempt to color or re-color this product.

Floor Protection Devices

- When moving in appliances or heavy furniture, it is always wise to protect the flooring and accessories from scuffing and tears by using something to protect the floor such as Masonite, Ram Board or heavy construction paper
- Use floor protectors under furniture or fixtures to reduce indentation; as a rule of thumb, the heavier the item the wider the floor protection device needed
- Place walk-off mats at outside entrances manufactured with non-staining backs to prevent discoloration