

1. PRODUCT NAME**Wood Elements Wall Base, 4" Cove****2. COMPANY INFORMATION**

Flexco Corporation

1401 East 6th Street

Tuscumbia, AL, USA 35674

Phone: (256) 383-7474; (800) 633-3151

Fax: (256) 381-0322; (800) 346-9075


Email: info@flexcofloors.com, technical@flexcofloors.comInternet: www.flexcofloors.com**3. PRODUCT DESCRIPTION**

ASTM F 1861, Type TP, Group 2, Style B


Thermoplastic Rubber Formulation designed to meet or exceed the above-mentioned standard specification for Resilient Wall Base.

Inside and Outside corners are available with a nominal 3" return.

WEC-XXX, 4" Cove



Available in 48" Lengths and 120' Coils

Color Sample:**4. TECHNICAL DATA****ASTM E 84 (NFPA 255)** - Class B**ASTM E 648 (NFPA 253)** - Class 1 > .45 W/cm²**ASTM E 662 (NFPA 258)** - Passes < 450**ASTM F 1861**- Meets or exceeds the requirements for heat & light aging, chemical resistance and dimensional stability**5. LEED INFORMATION**

May contribute to LEED® CI and NC credits MR 4, MR 5 and MR 6. For detailed LEED information, see

flexco.ecoscorecard.com**6. INSTALLATION**

Maintain the installation area, wall base, and adhesive between 65° F and 85° F for at least 48 hours before installation, during installation, and after the installation. Use only on structurally sound interior wall surfaces such as dry plaster, cured drywall, exterior grade plywood, concrete and masonry that are clean, smooth, dry and structurally sound. All surfaces must be free from moisture, alkali, old adhesive, dust dirt, wax, oil, grease, loose paint or plaster, nonporous wall coverings or paints and other extraneous coatings or materials that could prevent a successful bond. Any rough or uneven surfaces may telegraph through the wall base. Refer to Wood Elements Wall Base Installation instructions for detailed information.

7. ADHESIVES**Adhesive for Porous Substrates**

1100 Wall Base Adhesive is a premium solvent free Acrylic adhesive with aggressive wet suction grip for all Flexco Wall Base products. Coverages are described on the 1100 Wall Base Adhesive quick spec.

Adhesive for Non-Porous Substrates

Use a premium contact adhesive for installation over all non-porous substrates such as metal, FRP panels, etc.

8. PRODUCT MAINTENANCE

Refer to Flexco Wood Elements Wall Base Maintenance Information for detailed instructions

9. AVAILABILITY AND COST

Products are available through Flexco distributors. Contact Flexco Customer Service or visit www.flexcofloors.com for a list of distributors.

10. LIMITED WARRANTY

Limited Two (2) Year Warranty

