



### Manufacturer

Flexco Corporation  
1401 East 6th Street  
Tuscumbia, AL USA 35674  
Phone (800) 633-3151  
Fax (800) 346-9075  
Email: [info@flexcofloors.com](mailto:info@flexcofloors.com),  
[solutions@rhctechnical.com](mailto:solutions@rhctechnical.com)  
Internet: [www.flexcofloors.com](http://www.flexcofloors.com)

### Risers


Gauge: 1/8"  
Height: 7"  
Lengths: 36", 42", 48", 54", 60", 72", 84", 96"\* , 108"\*  
Pieces per carton: 24

\*Risers over 84" will be packaged 10 per carton.



### Stringers

Gauge: 0.080"  
Height: 10"  
Length: 72"  
Pieces per carton: 10



### TECHNICAL DATA

#### Classification; ASTM F1861 & ASTM F2169

Type TS; Rubber, Vulcanized Thermoset  
Group 1; Solid (homogeneous)  
Class 1; Smooth

**ASTM E 648 (NFPA 253), Critical Radiant Flux -**  
Class 1, > .45 W/cm<sup>2</sup>

**ASTM E 662 (NFPA 258), Smoke Generation -**  
Passes, < 450

**CAN/ULC-S102.2, Surface Burning - FSR**  
115, SDC 275

**ASTM F 925, Resistance to Chemicals -**  
Passes, List of Chemicals Available

**ASTM F 1514, Heat Stability of Color -  $\Delta E < 8$  Avg**

**Recommend Storage Temperature: 50° - 85° F**

**Acclimation Time: 48 Hours in Service Conditions**

**INSTALLATION** (Visit our website to refer to Rubber Stair Tread, Risers & Stringers Installation & Technical Data Sheet for complete Installation instructions)

We recommend Flexco Rubber Risers and Stringers be installed by a competent Commercial Flooring Contractor with previously demonstrated capabilities to install Rubber Stair Treads, Risers and Stringers. We recommend the installer and/or project manager have completed some type of formal training, such as FCICA CIM Program, CFI, INSTALL and/or Manufacturer's (even competitors) training program. To maintain full warranties for Flexco Rubber Stair Treads, Risers and Stringers all recommendations provided by Flexco must be followed.

### Approved Adhesives for Installation

- TP-620 Pressure Sensitive Tape
- AW-510 Acrylic Wet-Set Adhesive
- EW-710 Epoxy Wet-Set Adhesive
- C-630 Contact Adhesive

Failure to use Flexco recommended adhesives could result in voided product warranty

### PRODUCT MAINTENANCE

Refer to Flexco Rubber Stair Tread Maintenance Information for detailed instructions

### LIMITED WARRANTY

Limited Two (2) Year Warranty

*For complete adhesive, installation & maintenance instructions, visit [www.flexcofloors.com](http://www.flexcofloors.com)*