

#### PRIME SPORTS Recycled Rubber Flooring

##### Manufacturer

Flexco Corporation  
1401 East 6th Street  
Tuscumbia, AL USA 35674  
Phone (800) 633-3151  
Fax (800) 346-9075  
Email: [info@flexcofloors.com](mailto:info@flexcofloors.com), [solutions@rhctechical.com](mailto:solutions@rhctechical.com)  
Internet: [www.flexcofloors.com](http://www.flexcofloors.com)

##### Product Description

Prime Sports Recycled Rubber Tile is a rubber flooring product designed for interior and exterior sports and commercial applications. Prime Sports is PVC free and contains recycled content. Prime Sports has a non-porous surface which provides an excellent barrier to soil, spills, stains and odors. Because of its durability and resilience, Prime Sports is used in many professional sports facilities.



attach color submittal  
sample here

##### TECHNICAL DATA

ASTM F3041 - Bonded Crumb Rubber: Type I & II, Class A,B,C & D  
ASTMD2047 - Coefficient of Friction: > 0.8  
ASTM E648 (NFPA 253) - Critical Radiant Flux: Unclassified, 0.10 W/cm<sup>2</sup>  
ASTM D3389 - Abrasion Resistance: Passes  
ASTM F137 - Flexibility: Passes  
ASTM F970 - Static Load Limit: Passes, 250 PSI  
ASTM F2199 - Dimensional Stability: Passes  
ASTM F1514 - Heat Stability of Color: Passes  
ASTM F925 - Short Term Chem. Exposure: Passes (see ASTM F3041 Test)  
ASTM E492 Impact Sound Transmission: 57 IIC\*  
Time: 48 Hours  
Storage & Acclimation Temperature: 65 ° - 85 ° F  
*\* 6" Concrete, Drop Ceiling Assembly, 3/8" Material Only*

##### INSTALLATION\*

All materials are to be delivered to the installation location within 48 hours of installation in its original packaging with labels intact. Store products in a dry area protected from the weather with temperatures maintained between 65° F (19°C) and 85° F (30°C). DO NOT stack pallets. Remove all plastic wrapping and strapping from the pallets and un-box all material in the installation area at least 48 hours prior to installation.

##### APPROVED ADHESIVES\*

MS-700 Modified Silane  
EW-710 Epoxy Wet Set Adhesive  
U-705 Urethane Wet-Wet Adhesive

##### PRODUCT MAINTENANCE\*

Due to the natural tendencies of recycled rubber, all installations of Prime Sports Rubber Tiles are required to have the initial maintenance performed using the recommended procedures.

##### LIMITED WARRANTY

Flexco Provides a 3 year Limited Warranty. For additional information, see associated Warranty documents.

*\*For complete adhesive, installation & maintenance instructions, visit [www.flexcofloors.com](http://www.flexcofloors.com)*

##### Interlocking Tiles

Nominal Dimensions: 34 1/4" x 34 1/4" x 5/32", 1/4", 3/8", 1/2"  
Finish: Smooth  
Area per Tile: 8.2 sq. ft.

##### Square Edge Tiles

Nominal Dimensions: 36" x 36" x 5/22", 1/4", 3/8", 1/2"  
Finish: Smooth  
Area per Tile: 9 sq. ft.

##### Rolls

Nominal Dimensions: 48" x 24 3/4" - 49 1/2"  
Finish: Smooth  
Area per Tile: 99 - 198 sq. ft.