

Nominal Dimensions	4" (10.2 cm)
Nominal Length	48" (1.2 m) Cuts or 120' (36.6 m) Coils
Nominal Thickness	1/8" (3.2 mm)
OC (Outside Corners) Available	Yes
IC (Inside Corners) Available	Yes
ASTM F1861 - Resilient Wall Base	Type TP, Group 2 (Layered), Style B (Cove)
ASTM E648 (NFPA 253) - Critical Radiant Flux	Class 1, $\geq 0.45 \text{ W/cm}^2$
ASTM E662 (NFPA 258) - Smoke Density	Passes, ≤ 450
ASTM E84 - Surface Burning	Class A
CAN/ULC-S102.2 - Surface Burning	10 Flame Spread Rating, 60 Smoked Developed Classification
ASTM F925 - Chemical Resistance	Excellent with chemicals listed in standard, Additional chemicals available via chart
<i>ASTM F925 testing is utilized to ensure flooring materials will stand up to certain household standard chemistries. Additional chemical resistance testing performed using this test method is for informational and guidance purposes only. Proper maintenance will have an effect on chemical resistance, but the best defense against a negative effect is to clean the drop/spill from the flooring surface immediately.</i>	
ASTM F1515 - Light Stability	Excellent, $\Delta E \leq 8$
Attributes & Certifications	<p>Made in the U.S.A.</p> <p>Meets Buy America Act (49 CFR Part 661, 49 U.S.C. 5323)</p> <p>Meets Buy American Act (7 CFR Part 1787, 41 U.S.C 8301-8305)</p> <p>Meets Federal Acquisition Regulation (FAR 52.225-9)</p> <p>Manufactured in ISO 14001:2015 Certified Facility</p> <p>Contributes to LEED v4/4.1</p> <p>FloorScore Certification</p> <p>Meets CA 01350 Requirements</p> <p>Meets CHPS Requirements</p> <p>NSF/ANSI 332 Platinum Certification</p> <p>Contains No Recycled Content</p>
Acclimation Time	48 Hours
Service & Storage Temperature	60° - 85° F
<i>See installation document for full installation details regarding approved substrates, job site conditions and acclimation procedures.</i>	
Product Warranty	5 Year Commercial Warranty
<i>See product warranty for full details regarding limitations and warranty coverage.</i>	
Recommended Adhesives	<p>Excelsior WB-600, Wall Base Adhesive</p> <p>Excelsior C-631, Contact Adhesive</p>



Wood Elements Wall Base

TECHNICAL DATA

Technical Support

solutions@rhctechnical.com

Product Support

info@flexcofloors.com

Technical Documentation

www.flexcofloors.com