

Nominal Dimensions	2 1/2" (6.4 cm) Cove & Straight
	4" (10.2 cm) Cove & Straight
	4 1/2" (11.4 cm) Cove & Straight
	6" (15.2 cm) Cove & Straight

All Base 2000 Wall Base Products are 1/8" (3.2 mm) Nominal Thickness

Cove & Straight Base 2000 Wall Base Available in all Sizes in 48" (1.2 m) Sticks and/or 120' (36.6 m) Coils

OC (Outside Corners) Available in 2 1/2", 4", 4 1/2" & 6" Heights (6" OC Available in Cove Only)

IC (Inside Corners) Available in 2 1/2" & 4" Only

ASTM F1861 - Resilient Wall Base	Type TP, Group 2 (Layered), Styles A (Straight) & B (Cove)
ASTM E648 (NFPA 253) - Critical Radiant Flux	Class 1, $\geq 0.45 \text{ W/cm}^2$
ASTM E662 (NFPA 258) - Smoke Density	Passes, ≤ 450
ASTM E84 - Surface Burning	Class A
CAN/ULC-S102.2 - Surface Burning	10 Flame Spread Rating, 60 Smoked Developed Classification
ASTM F925 - Chemical Resistance	Excellent with chemicals listed in standard, Additional chemicals available via chart

ASTM F925 testing is utilized to ensure flooring materials will stand up to certain household standard chemistries. Additional chemical resistance testing performed using this test method is for informational and guidance purposes only. Proper maintenance will have an effect on chemical resistance, but the best defense against a negative effect is to clean the drop/spill from the flooring surface immediately.

ASTM F1515 - Light Stability	Excellent, $\Delta E \leq 8$
-------------------------------------	------------------------------

Attributes & Certifications	Made in the U.S.A.
	Meets Buy America Act (49 CFR Part 661, 49 U.S.C. 5323)
	Meets Buy American Act (7 CFR Part 1787, 41 U.S.C 8301-8305)
	Meets Federal Acquisition Regulation (FAR 52.225-9)
	Manufactured in ISO 14001:2015 Certified Facility
	Contributes to LEED v4/4.1
	FloorScore Certification
	Meets CA 01350 Requirements
	Meets CHPS Requirements
	NSF/ANSI 332 Platinum Certification
	HPD Available
	Contains No Recycled Content

Acclimation Time	48 Hours
-------------------------	----------

Service & Storage Temperature	60° - 85° F
--	-------------

See installation document for full installation details regarding approved substrates, job site conditions and acclimation procedures.



Base 2000 Wall Base

TECHNICAL DATA

Product Warranty	5 Year Commercial Warranty
-------------------------	----------------------------

See product warranty for full details regarding limitations and warranty coverage.

Recommended Adhesives	Excelsior WB-600, Wall Base Adhesive Excelsior C-631, Contact Adhesive
------------------------------	---

Technical Support	solutions@rhctechnical.com
--------------------------	--

Product Support	info@flexcofloors.com
------------------------	--

Technical Documentation	www.flexcofloors.com
--------------------------------	--