

Nominal Dimensions

Covers 1/4" (6.4 mm) From Wall

<i>Charmed</i>	4" (10.2 cm) Height x 8' (2.4 m) Length
<i>Captivate</i>	4.25" (10.8 cm) Height x 8' (2.4 m) Length
<i>Noble</i>	5.25" (13.3 cm) Height x 8' (2.4 m) Length
<i>Escalate</i>	6" (15.2 cm) Height x 8' (2.4 m) Length
<i>Reflection</i>	7.75" (19.7 cm) Height x 40' (12.2 m) Length

Covers 3/8" (9.5 mm) From Wall

<i>Harmony</i>	2.675" (6.8 cm) Height x 40' (12.2 m) Length
<i>Regal</i>	3" (7.6 cm) Height x 8' (2.4 m) Length
<i>Echo</i>	4" (10.2 cm) Height x 8' (2.4 m) Length
<i>Icon</i>	4" (10.2 cm) Height x 8' (2.4 m) Length
<i>Merit</i>	4.25" (10.8 cm) Height x 40' (12.2 m) Length
<i>Bliss</i>	4.5" (11.4 cm) Height x 8' (2.4 m) Length
<i>Charisma</i>	4.5" (11.4 cm) Height x 40' (12.2 m) Length
<i>Whimsical</i>	4.5" (11.4 cm) Height x 8' (2.4 m) Length
<i>Triumph</i>	4.675" (11.9 cm) Height x 8' (2.4 m) Length
<i>Enchanted</i>	5" (12.7 cm) Height x 8' (2.4 m) Length
<i>Marquis</i>	6" (15.2 cm) Height x 8' (2.4 m) Length
<i>Resolute</i>	6" (15.2 cm) Height x 8' (2.4 m) Length

Covers 1/2" (12.7 mm) From Wall

<i>Fascinate</i>	6" (15.2 cm) Height x 8' (2.4 m) Length
<i>Quarter Round</i>	1/2" (12.7 mm) Height x 1/2" (12.7 mm) Width

ASTM F1861 - Resilient Wall Base	Type TP, Group 2, Style D
ASTM E648 (NFPA 253) - Critical Radiant Flux	Class 1, $\geq 0.45 \text{ W/cm}^2$
ASTM E662 (NFPA 258) - Smoke Density	Passes, ≤ 450
ASTM E84 - Surface Burning	Class A
CAN/ULC-S102.2 - Surface Burning	10 Flame Spread Rating, 60 Smoked Developed Classification
ASTM F925 - Chemical Resistance	Excellent with chemicals listed in standard, Additional chemicals available via chart
<i>ASTM F925 testing is utilized to ensure flooring materials will stand up to certain household standard chemistries. Additional chemical resistance testing performed using this test method is for informational and guidance purposes only. Proper maintenance will have an effect on chemical resistance, but the best defense against a negative effect is to clean the drop/spill from the flooring surface immediately.</i>	
ASTM F1515 - Light Stability	Excellent, $\Delta E \leq 8$



Base Sculptures Profiled Wall Base

TECHNICAL DATA

Attributes & Certifications

Made in the U.S.A.

Meets Buy America Act (49 CFR Part 661, 49 U.S.C. 5323)

Meets Buy American Act (7 CFR Part 1787, 41 U.S.C 8301-8305)

Meets Federal Acquisition Regulation (FAR 52.225-9)

Manufactured in ISO 14001:2015 Certified Facility

Contributes to LEED v4/4.1

FloorScore Certification

Meets CA 01350 Requirements

Meets CHPS Requirements

NSF/ANSI 332 Platinum Certification

HPD Available

Contains No Recycled Content

Acclimation Time

48 Hours

Service & Storage Temperature

60° - 85° F

See installation document for full installation details regarding approved substrates, job site conditions and acclimation procedures.

Product Warranty

10 Year Commercial Warranty

See product warranty for full details regarding limitations and warranty coverage.

Recommended Adhesives

Excelsior WB-600, Wall Base Adhesive

Excelsior C-631, Contact Adhesive

Technical Support

solutions@rhctechnical.com

Product Support

info@flexcofloors.com

Technical Documentation

www.flexcofloors.com