


# #163 Snap-Down T-Edge Divider

## Manufacturer

Flexco Corporation 1401 East 6th Street Tuscumbia, AL USA 35674 Phone (800) 633-3151 Fax (800) 346-9075 Email: <u>info@flexcofloors.com</u>, <u>solutions@rhctechnical.com</u> Internet: <u>www.flexcofloors.com</u>

## **Product Description**

Co-Extruded Thermoplastic formulation designed to provide excellent resistance to scuffing and gouging while meeting ADA recommendations for transitioning different flooring surfaces



Attach color submittal sample here

#### **Technical Data**

ASTM E84 - Surface Burning: Class A ASTM E648 (NFPA 253) - Critical Radiant Flux: Class I, > .045 W/cm2 ASTM E662 (NFPA 258) - Smoke Density: Passes, <450 Acclimation Time: 48 Hours Storage & Acclimation Temperature: 65 ° - 85 ° F

#### Adhesives\*

T-Edge Divider Snaps into the 101 or 102 single flange tracks.

## Installation\*

Vinyl Accessories are designed for interior use only with temperatures maintained from 65°F (19°C) and 85°F (30° C). The flooring installer must inspect all material for manufacturing imperfections and irregularities prior to installation. Before installing, confirm accessory placement and the placement of adjoining material per design specifications.

#### Maintenance\*

Wipe the Vinyl Flooring Accessories with a mild solution of Neutral pH cleaner such as Excelsior NC-900 or equivalent. Do not use detergents, abrasive cleaners or "mop and shine" products; they will dull the look of the flooring.

## **Technical Document Support**

Additional product resources and technical documents are available online at: <u>www.flexcofloors.com</u> For additional technical support, send an e-mail to: <u>solutions@rhctechnical.com</u>

## Warranty

FLEXCO Provides a 1 year Limited Warranty on all Vinyl Accessories. For additional information, see associated Warranty documents.

\*For complete adhesive, installation & maintenance instructions, visit <u>www.flexcofloors.com</u>