

## **Fascinate**

## BASE SCULPTURES PROFILED WALL BASE SUBMITTAL SPECIFICATION

| Nominal Height  | 6" (15.2 cm)   |
|---|--|
| Nominal Length  | 8' (2.4 m)   |
| Nominal Thickness (Expansion Gap Coverage                         | ) 1/2" (15.2 cm)   |
| ASTM F1861 - Resilient Wall Base                                  | Type TP, Group 2, Style D  |
| ASTM E648 (NFPA 253) - Critical Radiant Flux                      | Class 1, ≥ 0.45 W/cm <sup>2</sup>  |
| ASTM E662 (NFPA 258) - Smoke Density                              | Passes, ≤ 450  |
| ASTM E84 - Surface Burning  | Class A  |
| CAN/ULC-S102.2 - Surface Burning                                  | 10 Flame Spread Rating, 60 Smoked Developed Classification   |
| ASTM F925 - Chemical Resistance                                   | Excellent with chemicals listed in standard, Additional chemicals available via chart  |
|   | stand up to certain household standard chemistries. Additional chemical resistance testing<br>ance purposes only. Proper maintenance will have an effect on chemical resistance, but the best<br>n the flooring surface immediately. |
| ASTM F1515 - Light Stability                                      | Excellent, ∆E ≤ 8  |
| Attributes & Certifications                                       | Made in the U.S.A.   |
|   | Meets Buy America Act (49 CFR Part 661, 49 U.S.C. 5323)  |
|   | Meets Buy American Act (7 CFR Part 1787, 41 U.S.C 8301-8305)   |
|   | Meets Federal Acquisition Regulation (FAR 52.225-9)  |
|   | Manufactured in ISO 14001:2015 Certified Facility  |
|   | Contributes to LEED v4/4.1   |
|   | FloorScore Certification   |
|   | Meets CA 01350 Requirements  |
|   | Meets CHPS Requirements  |
|   | NSF/ANSI 332 Platinum Certification  |
|   | HPD Available  |
|   | Contains No Recycled Content   |
| Acclimation Time  | 48 Hours   |
| Service & Storage Temperature                                     | 60° - 85° F  |
| See installation document for full installation details regarding | approved substrates, job site conditions and acclimation procedures.   |
| Product Warranty  | 10 Year Commercial Warranty  |
| See product warranty for full details regarding limitations and   | warranty coverage.   |
| Recommended Adhesives   | Excelsior WB-600, Wall Base Adhesive   |
|   | Excelsior C-631, Contact Adhesive  |



## **Fascinate**

## BASE SCULPTURES PROFILED WALL BASE SUBMITTAL SPECIFICATION

| Technical Support       | solutions@rhctechnical.com |
|-------------------------|----------------------------|
| Product Support         | info@flexcofloors.com      |
| Technical Documentation | www.flexcofloors.com       |



