

Whimsical

BASE SCULPTURES PROFILED WALL BASE SUBMITTAL SPECIFICATION

Nominal Height	4 1/2" (11.4 cm)
Nominal Length	8' (2.4 m)
Nominal Thickness (Expansion Gap Cover	age) 3/8" (9.5 mm) @ Thickest Dimension
ASTM F1861 - Resilient Wall Base	Type TP, Group 2, Style D
ASTM E648 (NFPA 253) - Critical Radiant F	lux Class 1, ≥ 0.45 W/cm ²
ASTM E662 (NFPA 258) - Smoke Density	Passes, ≤ 450
ASTM E84 - Surface Burning	Class A
CAN/ULC-S102.2 - Surface Burning	10 Flame Spread Rating, 60 Smoked Developed Classification
ASTM F925 - Chemical Resistance	Excellent with chemicals listed in standard, Additional chemicals available via chart
	will stand up to certain household standard chemistries. Additional chemical resistance testing guidance purposes only. Proper maintenance will have an effect on chemical resistance, but the best I from the flooring surface immediately.
ASTM F1515 - Light Stability	Excellent, ∆E ≤ 8
Attributes & Certifications	Made in the U.S.A.
	Meets Buy America Act (49 CFR Part 661, 49 U.S.C. 5323)
	Meets Buy American Act (7 CFR Part 1787, 41 U.S.C 8301-8305)
	Meets Federal Acquisition Regulation (FAR 52.225-9)
	Manufactured in ISO 14001:2015 Certified Facility
	Contributes to LEED v4/4.1
	FloorScore Certification
	Meets CA 01350 Requirements
	Meets CHPS Requirements
	NSF/ANSI 332 Platinum Certification
	HPD Available
	Contains No Recycled Content
Acclimation Time	48 Hours
Service & Storage Temperature	60° - 85° F
See installation document for full installation details regar	ding approved substrates, job site conditions and acclimation procedures.
Product Warranty	10 Year Commercial Warranty
See product warranty for full details regarding limitations	and warranty coverage.
Recommended Adhesives	Excelsior WB-600, Wall Base Adhesive
	Excelsior C-631, Contact Adhesive



BASE SCULPTURES PROFILED WALL BASE SUBMITTAL SPECIFICATION

Technical Support	solutions@rhctechnical.com
Product Support	info@flexcofloors.com
Technical Documentation	www.flexcofloors.com

Attach Color Sample Here

