



FlexTuft Recycled Rubber Tile

TECHNICAL DATA

Finish	Ribbed Tufted Surface
Nominal Dimensions	12" x 12" x 3/8" (Nominal)
Backing	Vulcanized or Non-Vulcanized
ASTM D2859 - Ignition Characteristics	Passes, (FF1-70, 16 CFR 1630)
ASTM E662 (NFPA 258) - Smoke Density	Passes, ≤ 450
Acclimation Time	48 Hours
Service & Storage Temperature	60° - 85° F

See installation document for full installation details regarding approved substrates, job site conditions and acclimation procedures.

Product Limitations	<p>Due to the recycled nature of this product, color variation can be present from piece to piece.</p> <p>Outdoor Installation, Exposure to Sunlight, and Foot Traffic will cause discoloration and the material to fade to the natural color due to the process of dyeing the material. It will resort back to the natural color of the tire cord. We do not recommend the application of Dyes to re-color product after fading.</p> <p>Material installed in outdoor application or indoors within 20' of entryways must be the Vulcanized product and we recommend the Tweed color.</p> <p>Non-Vulcanized material is for indoor applications only, not recommended within 20' of entryways.</p>
----------------------------	---

Product Warranty	5 Year Commercial Warranty
-------------------------	----------------------------

See product warranty for full details regarding limitations and warranty coverage.

Recommended Adhesives	<p>Excelsior PS-525, Modified Pressure Sensitive (ONLY approved for Non-Vulcanized Indoor Installations)</p> <p>Excelsior U-705, Urethane Wet-Set</p> <p>Excelsior EW-710, Urethane Enhanced Epoxy Adhesive</p>
------------------------------	--

Attributes & Certifications	<p>Made in the U.S.A.</p> <p>Meets Buy America Act (49 CFR Part 661, 49 U.S.C. 5323)</p> <p>Meets Buy American Act (7 CFR Part 1787, 41 U.S.C 8301-8305)</p> <p>Meets Federal Acquisition Regulation (FAR 52.225-9)</p> <p>Contributes to LEED v4/4.1</p> <p>90% Post-Consumer Recycled Content</p>
--	---

Technical Support	solutions@rhctechnical.com
--------------------------	--

Product Support	info@flexcofloors.com
------------------------	--

Technical Documentation	www.flexcofloors.com
--------------------------------	--